

RFL® 9508 PLC

Ordering Information

RFL Part Number (fill in blanks):

9508

Base System								
Chassis								
Power Supply								
38-150 Vdc		A						
200-300 Vdc		B						
RF Power Options								
50W			0					
100W			1					
Integral Teleprotection Modules								
None			0					
One			1					
Two			2					
Teleprotection I/O (Select 2)								
None or External (if External choose Drop and Insert Mode)			0					
PLC-TT w/2 function Solid State 48/125 Vdc			1					
PLC-TT w/2 function Solid State 250 Vdc			2					
PLC-TT w/4 function Solid State 48/125 Vdc			3					
PLC-TT w/4 function Solid State 250 Vdc			4					
PLC-TT w/2 function Relay 48/125 Vdc			5					
PLC-TT w/2 function Relay 250 Vdc			6					
PLC-TT w/4 function Relay 48/125 Vdc			7					
PLC-TT w/4 function Relay 250 Vdc			8					
Drop and Insert Mode								
None			0					
Electrical T1/E1 (MA-278)			A					
Electrical E1 75 ohm (MA271)			B					
Fiber 820 nm Multimode			C					
Fiber 1300 nm LED singlemode			D					
Fiber 1300 nm Laser singlemode			E					
Fiber 1550 nm Laser singlemode			F					
PLC Audio Options (Select 2) Note: If orderwire is required a VF-5XP must be selected.								
None			0					
Speech Plus with comp. blocks(VF-5XP, MA-301B)			A					
Speech Plus with screw terminals (VF-5XP, MA-301A)			B					
Speech with comp. blocks (VF-5C, MA-301B)			C					
Speech with 50 Pin telco (VF-5C, MA-301)			D					
Speech with screw terminals (VF-5C, MA-301A)			E					
FXO with Modular Jacks (VF-15C-1, MA-303)			F					
FXS with Modular Jacks (VF-16B-1, MA-303)			G					
Orderwire with comp. blocks (VF-6I, MA-301B)			H					
Orderwire with screw terminals (VF-6I, MA-301A-1)			J					
Selective Calling Module (VF-8A, MA-306)			K					
Special Options								
None			0					
Special Configuration			X					
Ethernet remote access (MA-490)			1					