

RFL® 9785 On / Off Powerline Carrier Ordering Information

RFL Part Number (fill in blanks):

9785

--	--	--	--	--	--	--	--	--	--

Basic Transmitter/Receiver	
Chassis, motherboard & standard modules	9785
Power Supply	
48 to 125 Vdc Single Supply	1
48 to 125 Vdc Dual Supplies	2
250 Vdc Single Supply	3
250 Vdc Dual Supplies	4
Power Amplifier and Power Output Filter	
10 W, 30 to 65 KHz	1
10 W, 65 to 156 KHz	2
10 W, 156 to 392 KHz	3
10 W, 392 to 535 KHz	4
10 W, 114 to 288½ KHz	5
50 W, 20 to 500 KHz w/RX Conn, No Atten/RX Filter	7
100 W, 20 to 500 KHz w/RX Conn, No Atten/RX Filter	8
Relay I/O Voltage	
48 Vdc	1
125 Vdc	2
250 Vdc	3
Logic Level Interface 48 Vdc	4
Logic Level Interface 125 Vdc	5
Logic Level Interface 250 Vdc	6
Receive Bandwidth	
500 Hz	1
1000 Hz	2
1500 Hz	3
Sequence of Events Option	
No Sequence of Events Option	1
Sequence of Events Option w/RPM	2
Checkback Options	
No Checkback Option	1
Checkback Option	2
Checkback with Aux. Alarm Chassis	3
Price Reduction for SOE and Checkback Option	N/A
Voice	
No Voice Functions	0
With Voice Functions	1
Current Limit	
No Current Limit Module	0
48 Vdc Current Limit Module	1
125 Vdc Current Limit Module	2
Other Custom Configuration	
No user specified customization	A
RF Line I/O with one UHF Port	B
Additional system details provided by customer	Z